

2019 HINO 268

GVW: 25,950 LBS. BBC: 108"

ENGINE MODEL: J08E-VB 260HP 660 LB-FT TORQUE (AVAILABLE)

HINO 

TRUCKS

A Toyota Group Company

HINO INSIGHT CONNECTED VEHICLE



INSIGHT

WWW.HINO.COM

TELEMATICS, CASE MANAGEMENT, REMOTE DIAGNOSTICS...**STANDARD.**

At Hino we're changing the way we support our vehicles and customers so that your business is first. From the moment you take delivery of your Hino Insight equipped connected vehicle, you're on the road to more uptime and lower operating costs. Combining Telematics, Remote Diagnostics and Case Management in one integrated platform, Hino Insight puts critical vehicle and driver management tools at your fingertips.



2019 HINO 268



ENGINE		
Model	STD Hino J08E-WU	OPT Hino J08E-VB
Max. output at 2,500 rpm (SAE Gross)	230hp	260hp
Max. torque at 1,500 rpm (SAE Gross)	520 lb.-ft.	660 lb.-ft.
Type	Diesel 4-cycle, 6 cylinder in-line, water-cooled, dry cylinder liners	
Fuel System	Common rail, direct injection type (Denso)	
Engine displacement	8L	
Bore and Stroke	4.41 x 5.12 in.	

WHEELS/TIRES/BRAKES	
---------------------	--

6 Wheels	STD Steel 22.5X8.25 10-stud disc powder coated white OPT Powder coated gray, or Polished aluminum
6 Tires	STD 11R22.5-14, Fr-Rib, Rr-All Season OPT 255/70R22.5-16, Fr-Rib, Rr-All Season OPT 295/75R22.5-14, Fr-Rib, Rr-All Season
Service brake	Hydraulic system with disc brake for front and rear wheels
Exhaust brake	Electric-pneumatic with valve in exhaust pipe
Parking brake	Lever control with cable, internal expanding drum type

POWERTRAIN AND PERFORMANCE

Transmission	Type	Six speed automatic					
	Model	STD Allison 2200RDS with Fuelsense 2.0			OPT Allison 2500RDS with Fuelsense 2.0		
Ratios	1st	3.102			3.512		
	2nd	1.811			1.896		
	3rd	1.406			1.439		
	4th	1			1		
	5th	0.712			0.737		
	6th	0.614			0.64		
	Rev.	-4.492			-5.086		
GVW (lbs.)		25,950			25,950		
GCWR* (lbs.)		26,000			26,000		
230 HP	Rear Axle Gear Ratios	OPT 4.63	OPT 4.88	OPT 5.13	STD 4.11	OPT 4.33	OPT 4.63
	Gradeability (% of grade)	36.5	38.8	41.2	36.7	39	42.3
260 HP	GCWR* (lbs.)	26,000			33,000		
	Rear Axle Gear Ratios	OPT 4.63	OPT 4.88	OPT 5.13	STD 4.11	OPT 4.33	OPT 4.63
	Gradeability (% of grade)	48.6	52	55.5	48.9	52.3	57.2

DIMENSIONS/WEIGHTS

Wheelbase (in.)	152/G	175/J	187/L	205/M	212/N	217/P	235/R	253/T	271/V
Useable cab to axle (in.)	84.6	107.6	119.6	137.6	144.6	149.6	167.6	185.6	203.6
Rear overhang (in.)	50	63	75	75	50	97	97	97	79
Frame height at front axle (in.)	37	37	37	37	37	37	37	37	37
Frame height at rear axle (in.)	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
Std. chassis weight (lbs.)	9,920	9,865	9,920	10,030	9,985	10,140	10,185	10,220	10,285

FRAME		
Ladder type	Straight C channel	
Width (in.)	34	
Yield strength (PSI)	80,000	
Resisting bending moment (one side, no reinforcement) in.-lbs.	152" WB	All others
	1,280,000	1,031,900

AXLE/SUSPENSION

Front axle	MFS-10 series reverse Elliot, "I" beam (oil lubricated)	
Front spring	Taper-leaf springs with shock absorbers	
Rear axle	RS17-145, full floating, single reduction, single-speed, hypoid gearing	
Rear Suspension	STD Spring Semi-elliptic main OPT Air ride suspension - Hendrickson OPT Air ride suspension - dump valve (electric), single & dual valve	

WEIGHT CAPACITIES

Front axle/susp	lbs.	10,000/12,000
Rear axle/susp	lbs.	19,000/19,000

CHASSIS EQUIPMENT

Fuel Tank	STD 50 gallon OPT Dual 50 gal./Single 70 gal./Single 95 gal.	
DEF tank	4.7 gal.	

ELECTRICAL EQUIPMENT

Batteries	STD Two, parallel connection, 1300 CCA (GR 31) OPT Multiple two battery choices OPT Multiple Three battery choices	
Alternator	STD 12V, 130A, Delco (brush) OPT 12V, 135A (brushless)/180A (brush)/200A (brush)	
Starter	Denso-12V, 4.8kW	

WHY DRIVERS LOVE OUR TRUCKS

Bluetooth AM/FM radio with CD player
Air Ride Drivers Seat
Air Conditioning
Cruise Control
Tilt and Telescopic Steering Wheel
55 Degree wheel cut
80 Degree Door Opening
4007 sq. in. windshield area

WHY OWNERS LOVE OUR TRUCKS



ENGINE WARRANTY	STD - 5 years/250,000 miles OPT - 7 years/150,000 miles
HINOCARE	OPT - Preventive care extension
HINOWATCH	24/7 Roadside Assistance
HINO INSIGHT	Telematics by Telogis Remote Diagnostics Case Management
	STD 1 Year OPT 3 & 5 Yr STD 5 Years STD 5 Years

POPULAR OPTIONAL EQUIPMENT (partial list)

Allison Fuel Sense Plus / Max
Anti-siphon device insert in fuel tank
Back-up alarm
Cab paint, exterior - custom (factory)
Engine idle shutdown
Exhaust system - vertical stack type
Mirrors, fender mounted-chrome (both sides or passenger only)
Mirrors, outside rearview-chrome
Mirrors-power heated (available in chrome)
Power windows and door locks (available with keyless entry)
Programmable speed limit 65,70 mph
Rear helper spring-sub leaf type
Stabilizer bar, rear (leaf suspension only)